



ABOVE-GROUND AUTOMATIC SLATTED COVER

CONTURA



An innovative design which fits large sized pools

DEL

ABOVE-GROUND AUTOMATIC SLATTED COVER CONTURA

+ AESTHETICS


- Elegant and contemporary end-stands imagined by our own designers.
- Discretion assured with end-stands hiding the cover while the slat is rolled.

+ FINISHES

- All materials and components have been carefully selected for a perfect stability and an optimal rendering.
- Coloured grey aluminium end-stands have excellent strength to impacts and scratches, and a good UV durability.

+ CUSTOMISABLE

- Available in electric or solar version.



Cover available for pool from 2.00 x 3.00 m and up to 10.00 x 20.50 m.

1 END-STANDS

- Coloured aluminium grey end-stands.
- Excellent resistance to impacts and scratches.
- High UV durability.

2 MOTORISATION

Electric version:

- Adjustable mechanical ends-of-runs, removable without dismantling the reel system, freewheeling motor (used to unroll the slats in case of a breakdown and to keep the pool safe despite the absence of electricity).
- The lifetime of the motor is longer thanks to the bearings which support the tube and therefore the weight of the cover.

Solar version:

- The end-stand include one or three solar panels depending on the pool size.

Controlled by Wi-Key, key switch or LivePool.

3 LOCKING KITS

4 SLATS

- Solar polycarbonate slats or opaque 69 PVC slats.

5 ALUMINIUM TUBE


Your slats choice

All our slats have a quality finish and are compliant with the NF P 90-308 standard.

Solar polycarbonate slats



Opaque PVC slats



USEFUL TO KNOW

Choose solar polycarbonate slats to heat your pool water.

+ LivePool

Opening and closing of the automatic cover with a smartphone thanks to the LivePool application (except solar version).

DON'T FORGET

Protect your slats from UVs and dirt

with the IVERNEA winter shift or the IVERNEA PLUS 4-season protective shift.



Read carefully and keep for the future reference.

The Contura automatic cover is a swimming pool safety cover designed to prevent children under 5 years of age from accessing the pool. This product complies with the standard NF P 90-308. It is no substitute for common sense or individual responsibility. It is not intended either to be a substitute for parental and/or adult supervision, which is the essential factor for the protection of young children. A child can get drowned within less than 3 minutes ; no type of protection will ever replace the vigilance and supervision of responsible adults.

Warranty: 2 years for the reel system and 3 years for the motor. 3 years for opaque PVC slats and 5 years for solar polycarbonate slats, in accordance with our general sales terms.

Order form: to have a cover correctly adjusted to the pool, it is essential to provide a drawing of the pool with measurements taken every 1 meter. In accordance with the standard NF P 90-308, the gap between the inside of the pool and the edge of the cover must be less than 70 mm.

Operating time: for a pool of 5,00 x 10,00 m : 3 minutes for the automatic opening or closing and 30 seconds for the locking or unlocking of the safety kits. One person only can do the opening and closing of the Contura.

Use: for all seasons. For a proper functioning, maintain a constant water level corresponding to a normal filtration of the pool. It is essential to have a water level regulator. The water level have to comply with the technical notice.

Use limits: The installation of an automatic DEL cover on overflow pools and/or with a stair along the length (detachable side stair) does not comply with the standard NF P 90-308. Another safety device should be used in that case. Unless otherwise specified by the manufacturer, under water alarms are not compatible with DEL covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering net to protect the cover. If the water level is lowered so that the wall units are above the waterline, roll the cover in and secure the pool using a winter safety cover.

Packing list: for a swimming pool measuring 5,00 x 10,00 m. Slats: 5 packages: 5.10 x 0.25 x 0.20 m - 250 kg / Tube: 1 package: 5.46 x 0.20 x 0.20 m - 30 kg / End-stands: 1 pallet: 0.80 x 0.60 x 0.55 m - 40 kg / Total weight: 350 kg.

Manufacturer: DEL SAS - ZA La Croix Rouge 35530 Brécé - France / www.del-piscine.fr

FOR MORE INFORMATION PLEASE ASK YOUR POOL EXPERT

