

IN-GROUND AUTOMATIC SLATTED COVER

ROLLIN



The reference cover on the market, ideal for construction

DEL


IN-GROUND AUTOMATIC SLATTED COVER ROLLIN

+ RELIABLE

- The Rollin slatted cover, is manufactured in our workshops for 30 years. It is THE reference model on the market.
- All the cover's components have been carefully selected to ensure the greatest longevity of the Rollin slatted cover.

+ DISCREET

- The in-ground slatted cover is in a pit covered by a decking above the waterline. The motor is housed in a separate dry pit for easier access.
- The colours of the cover parts can be matched together for perfect integration (beam, beam's supports, decking, slats, locking kits, separating wall).



Cover available for pools from 3.00 x 3.00 m and up to 10.00 x 16.50 m.

- 1 MOTORISATION**
- Coupling of the salt electrolysis to the cover.
 - Automatic switch.
- Controlled by Wi-Key, key switch or LivePool.

- 2 WALL UNITS**

- 3 SLATS**
- Opaque PVC 84 slats, solar polycarbonate slats or opaque PVC 69 slats.

- 4 LOCKING KITS**

- 5 ALUMINIUM TUBE**

- 6 ANODISED ALUMINIUM BEAM**

- 7 TEAK WOOD OR ALUMINIUM DECKING**

- 8 STOP FLOW**
- Control of the filtration of the cover. It allows to stop the filter pump when the automatic cover motor is working.

Your slats choice

All our slats have a quality finish and are compliant with the NF P90-308 standard.

Opaque PVC 84 slats

The standard for in-ground automatic slatted covers




Solar polycarbonate slats



Opaque PVC 69 slats


Optional depending on your pool configuration (consult your swimming pool specialist)



USEFUL TO KNOW
Opt for solar polycarbonate slats to heat your pool water.

Why cover your pool?

- To reduce the water consumption by limiting the evaporation.
- To reduce the energy consumption.
- To make the cleaning easier & to reduce the use of chemical products.



Read carefully and keep for future reference.

Rollin is a safety cover for swimming pools, designed to keep children under the age of 5 out of the pool. This product is compliant with standard NF P90-308 if installed with the recommended safety locking kits. It is not a substitute for common sense or personal responsibility. It is no substitute for the vigilance of parents and/or responsible adults, which remains the essential factor for the safety of young children. A child can drown in less than 3 minutes; no type of preventive measures can replace the monitoring and vigilance of a responsible adult.

Warranty: 3 years for the motor in the dry pit. 3 years warranty on opaque PVC 84 slats and opaque PVC 69 slats and 5 years warranty on the solar polycarbonate slats. The roller is warranted for 2 years, in accordance with our general terms of sale.

Order form: for the cover to be properly adjusted to the swimming pool, it is essential to provide a drawing of the pool measured metre by metre. As specified by standard NF P90-308, the gap between the inner side of the pool and the edge of the cover must be less than 70 mm.

Time needed to operate a pool measuring 5.00 x 10.00 m: 3 minutes for automatic opening or closing and 30 seconds for locking or unlocking the locking kits. The Rollin can be opened or closed by one person.

Use: all year round. To keep your cover in good working conditions, maintain a constant water level that matches the normal filtration rate of the swimming pool. The use of a water level regulator is essential. It must comply with the instruction manual.

Serviceability limits: The installation of a cover on overflow pools and/or pools with steps on the length side (removable steps on the side) is not compliant with the NF P90-308 standard. In this case other compliant systems should be used. Unless otherwise specified by the manufacturer, immersion alarms are not compatible with automatic slatted covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering net to protect the cover. If the water level is lowered so that the wall units are above the waterline, roll the cover in and secure the pool using a winter safety cover.

Packing list: for a swimming pool measuring 5 x 10 m. Opaque PVC 84 slats: 4 packages: 5.10 x 0.39 x 0.11 m - 190 kg. / Solar polycarbonate slats and opaque PVC 69 slats: 5 packages: 5.10 x 0.25 x 0.20 m - 250 kg / Tube: 1 package: 5.10 x 0.15 x 0.15 m - 40 kg / Tube: 1 package: 5.10 x 0.15 x 0.15m - 34 kg / Decking: 1 pallet: 1.20 x 1.00 x 0.50 m - 100 kg / Motorisation kit: 1 package: 0.60 x 0.35 x 0.35 m - 20 kg / Beam support: 1 package: 0.30 x 0.20 x 0.20 m - 10 kg / Locking kits: 1 package: 0.30 x 0.20 x 0.20 m - 5 kg / Total weight: 400 - 410 kg.

Fabricant : DEL SAS - ZA La Croix Rouge 35530 Brécé - France / www.del-piscine.fr

LIVEPOOL

Opening and closing of the automatic cover with a smartphone thanks to the LivePool application.

DON'T FORGET

Protect your slat cover from UVs and dirt with the IVERNEA winter shift or the IVERNEA PLUS 4-season protective shift.

FOR MORE INFORMATION PLEASE ASK YOUR POOL EXPERT

