



ABOVE-GROUND AUTOMATIC SLATTED COVER

TIXIT



Innovative design to sublimate your garden

DEL

ABOVE-GROUND AUTOMATIC SLATTED COVER

TIXIT

+ AESTHETIC

- Elegant, discreet and 100 % recyclable end-stands imagined by our own designers.
- LED lighting to emphasize the end-stand pure design for the electric version.

+ CUSTOMISABLE

- Available in electric or solar version.
- For each version, a choice of 3 end-stand colours for a perfect integration in your garden.

+ FINISHES

- All materials and components have been carefully selected for a perfect stability and an optimal rendering.
- The textured power-coated aluminium finishing gives the end-stands a decidedly contemporary appearance.

Electric version




Solar version



POOL SOUND (OPTION)

The cover end-stand turns into a Bluetooth® speaker to play music in the garden using a quick and intuitive connection. Available exclusively for electric version.



Cover available for pool from 2.00 x 3.00 m and up to 5.00 x 13.50 m.

1 END-STANDS

- Coloured aluminium end-stands.
- Compact end-stands (98 x 175 mm).

2 DECORATIVE LED STRIP (12 V)

- On/Off switch on the end-stand.

3 MOTORISATION

Tubular electric motor:

- Adjustable mechanical ends-of-runs, free-wheeling motor (used to unroll the slats in case of a motor breakdown and to keep the pool safe despite the absence of electricity).
- The motor service life is longer thanks to the bearings which support the tube and therefore the weight of the cover.

Controlled by Wi-Key, key switch or LivePool.

4 LOCKING KITS

5 SLATS

- Opaque PVC 84 slats, solar polycarbonate slats or opaque PVC 69 slats.

6 ALUMINIUM TUBE



LivePool

Opening and closing of the automatic cover with a smartphone thanks to the free LivePool App (except solar version).

Your slats choice

All our slats have a quality finish and are compliant with the NF P90-308 standard.

Opaque PVC 84 slats



White



Grey

Opaque PVC 69 slats



White



Beige



Grey



Blue

Solar polycarbonate slats




Absolute black



Crystal black




Crystal blue



Crystal brown



Silver



Crystal



Crystal green

USEFUL TO KNOW

Choose solar polycarbonate slats to heat your pool water.



Read carefully and keep for future reference

The Tixit automatic cover is a swimming pool safety cover designed to prevent children under 5 years of age from accessing the pool. This product complies with the standard NF P90-308. It is no substitute for common sense or individual responsibility. It is not intended either to be a substitute for parental and/or adult supervision, which is the essential factor for the protection of young children. A child can get drowned within less than 3 minutes; no type of protection will ever replace the vigilance and supervision of responsible adults.

Warranty: 2 years for the reel system and 3 years for the motor. 3 years for opaque PVC slats and 5 years for solar polycarbonate slats, in accordance with our general sales terms.

Order form: to have a cover correctly adjusted to the pool, it is essential to provide a drawing of the pool with measurements taken every 1 meter. In accordance with the standard NF P90-308, the gap between the inside of the pool and the edge of the cover must be less than 70 mm.

Operating time: for a pool of 5.00 x 10.00 m : 3 minutes for the automatic opening or closing and 30 seconds for the locking or unlocking of the safety kits. Tixit can be opened and closed by one person.

Use: for all seasons. For a proper functioning, maintain a constant water level corresponding to a normal pool filtration. It is essential to have a water level regulator. The water level have to comply with the technical notice.

Use limits: DEL automatic slatted covers on infinity pools can only be compliant if the pool is equipped with a device such as an Infinity control box that automatically lowers the water level by at least 2 cm when the cover is closed on the pool. To this day, DEL automatic slatted covers with a removable shape on a side staircase are not compliant with standard NF P90-308. Unless specified by the manufacturer, immersion alarms are not compatible with DEL automatic slatted covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering shift to protect the cover. If the water level falls, to keep the white goods out of the water, roll in the cover and secure the pool using a safety winter cover.

Packing list: for a swimming pool measuring 5.00 x 10.00 m. Slats: 5 packages of 5.10 x 0.25 x 0.20 m - 250 kg / Tube: 1 package of 5.46 x 0.20 x 0.20 m - 30 kg / End-stands: 1 pallet of 0.80 x 0.60 x 0.55 m - 40 kg / Total weight: 320 kg.

Manufacturer: DEL SAS - ZA La Croix Rouge - 35530 Brécé - FRANCE / www.del-piscine.fr/en



DON'T FORGET

Protect your slats from
UVs and dirt

with the Ivernea winter shift
or the Ivernea Plus 4-season
protective shift.

FOR MORE INFORMATION PLEASE ASK YOUR POOL EXPERT

DEL SAS with a capital of 2 300 000 € - RCS 303355671 Rennes - ZA La Croix Rouge - 35530 Brécé - FRANCE • Non-binding document • © DEL SAS, Arnaud Bertrand • 01/24 • Do not throw away



a brand by



A-DBRO12205.L1