

USER MANUAL

CARE/MAINTENANCE/SAFETY INSTRUCTIONS



AUTOMATIC COVER

To be provided to the customer

CONTENTS

PLEASE READ THESE INSTRUCTIONS CAREFULLY AND KEEP THEM FOR FUTURE REFERENCE

Please read this manual carefully to help you understand all of the information and to ensure safe installation, use and servicing. We are not held liable for any damage arising due to a failure to respect the instructions set out in this manual.

USE.....	3
Opening/closing the pool.....	3
Pushlock locking and unlocking.....	5
CARE / MAINTENANCE	6
Pool water level.....	6
Filtration & water treatment.....	7
Care (responsibility of the customer)	8
Maintenance (at least once a year)	9
Winterising.....	10
SERVICING/MAINTENANCE.....	11
Spare parts.....	11
Pièces détachées.....	11
REPAIR	12
REGULATIONS.....	13
Warranty condition.....	13
SAFETY ADVICE	14
RECYCLING	16
Packaging	16
End of life	16

OPENING/CLOSING THE POOL



Always check that the pool water level is constant and is in line with the recommendations set out in the manual.



The person performing the manoeuvre must ensure that no swimmers are present and must keep their eyes on the pool when opening and closing it.

- It is essential that the slatted cover be fully opened or closed. Never leave it halfway open.
- When using an automatic cleaner under the cover, check that the hose does not interfere with the movement of the slats when opening and closing the cover.
- It is essential that floating objects be removed from the surface of the water when closing the cover.
- Do not obstruct the cover during rolling or unrolling.
- Do not operate the cover when it is frozen over.
- Closing: approximately a few minutes for closing the cover and locking the attachment kits (for a 5.00 x 10.00 m pool).
- Opening: approximately a few minutes for unlocking the attachment kits and automatic cover opening (for a 5.00 x 10.00 m pool). This duration increases for larger pools and/or more powerful motors

WHEN OPENING - **Always lock the cover before starting the motor.**

- Unlock all attachment systems.
- Operate the open command.
- Store unlocking tools out of reach of children.
- Lock the Wi-Key command or store the key.

CLOSING

- Operate the closing command "contact maintained when closing".
- Lock all attachment systems.
- Store unlocking tools out of reach of children.
- Lock the Wi-Key command or store the key.




USE

- Never cover a slatted cover with a product not designed for this purpose, as the slats may become deformed, with the exception of Ivernée (in autumn and winter) and Ivernée Plus (in all seasons).
- Never leave an object on the cover (towel, rubber ring, etc.) because strong sunlight can cause the slats to expand locally and the warranty will no longer be valid.
- Solar polycarbonate slats are not compatible with bromine or bromine-containing treatments.
- Do not put any undiluted chemical product in direct contact with the solar polycarbonate slats (e.g. anti-algae).
- It is essential to carry out a test on a small area beforehand.)
- The water level must be maintained when the cover is installed.



USE

PUSHLOCK LOCKING AND UNLOCKING

LOCKING



UNLOCKING



An instructional video is available via the attached QR code.



<https://youtu.be/eoYalRbMWVE>

CARE / MAINTENANCE

Any person working on the electrical parts must be qualified and must comply with the manufacturer's instructions and with the standards and regulations in force.

During any work, the technician must wear his PPE (personal protective equipment): gloves, glasses, mat, etc.



We recommend cutting off power to the installation before any work.

The appliance must be disconnected from its power source during maintenance and when parts are being replaced.

The plug must be removed from the power source so that the operator can check from any accessible point that the plug remains disconnected.

POOL WATER LEVEL

- In order to ensure maximum safety and correct operation of the rewinder, always check that the water level in the pool remains constant and complies with the manufacturer's requirements (for greater comfort, use an overflow and a water level regulator).
- A water level that is too high is due to the overflow being obstructed by leaves or other items.
- A water level that is too low means that there is a risk of blockage.
- In case of a recess or a handrail, the water level must be controlled by a level regulator.
- Complying with the recommended minimum and maximum water levels ensures proper operation and compliance with the requirements of standard NF P90-308.
- It is advisable to pay close attention to fluctuations in the water level. The most suitable method (to ensure both monitoring and the necessary corrections) is to combine an overflow system with automatic filling.
- The target water level is specific to each pool and depends on the overall configuration of the cover. It is necessary to combine the recommendations relating to the reel and its possible decking with those relating to safety locks and slats.
- The NF P90-308 standard requirements imply compliance with the recommendations throughout the year and therefore an active winterisation without lowering the water level is needed.
- The water level must be less than 25 cm below the deck; beyond this, please consult us.
- If a safety system is installed on the pool, refer to the recommended water level indicated for that system.

CARE / MAINTENANCE

FILTRATION & WATER TREATMENT

- Schedule filtering during the hours the pool receives direct sunlight and have it running constantly when the water reaches 28°C.
- In order to guarantee the longevity of your installation, the pool water must be correctly treated according to the standards and recommendations in force (NF EN 16713-3)
- The pH, TH and TAC of the water should be checked and adjusted as often as necessary (however, care should be taken not to correct these 3 parameters independently of each other, but to do so using the Taylor table and balance the water according to the 3 parameters analysed).

CARE / MAINTENANCE

CARE (RESPONSIBILITY OF THE CUSTOMER)

- Clean your slatted cover thoroughly twice a year (when opening the pool for the season and when winterising it). This is even more important if your pool water is hard. To do this, use a descaling cleaner (see catalogue) and rinse with a water spray.
- Also take care to clean the attachment systems regularly, especially the piton, so that it does not become blocked. We recommend that you lubricate the hooks annually to ensure optimum performance.
- Inspect the entire system if an abnormal load is placed on the cover (such as in the event of a fall).
- Inspect the straps annually.
- Do not wash IPE duckboard with a high pressure washer, we recommend washing them regularly with clean water and a non metallic brush.
- Do not run, walk with care, the surface of the gratings can be made slippery by poor maintenance.
- Take care to clean the gratings regularly so that their surfaces do not become slippery.
- If the gratings become slippery, remove them and clean them mechanically.
- Before using shock chlorine, make sure you leave your pool in the open air and avoid covering it with a liner, bubble or closed cover.

CARE / MAINTENANCE

MAINTENANCE (AT LEAST ONCE A YEAR)

- All repairs must be carried out by a professional, who will contact the manufacturer if necessary (contact details on the back of the document).
- All spare parts must be original or comply with standard NF P90-308.
- Check the correct functioning of the installation.
- Inspect the entire cover.
- At the start of the season and in the event of an incident (a person falling, hail on the cover, abnormal force on the cover, etc.), it is essential to check that the slats do not show any visible damage that could compromise the cover's safety function (slats with cracks, holes, distortion, etc.). Replace the slats or the entire cover if necessary.
- In summer and winter, do not cover the cover with an opaque tarpaulin: the rise in temperature could damage the slats
- Check the condition of the straps (seams) and in particular the level of wear of the anti-abrasion sleeve. If this no longer fulfils its function of protecting the strap in contact with the lip from abrasion, replace it.
- Check the tightness of the electrical connections once a year.
- After-sales service: contact details on the back of the document.

CARE / MAINTENANCE

WINTERISING

- Winterise the pool in a way that is suited to its geographical location.
- Close the cover in the safety position without lowering the water level.
- If the water level drops, roll up the shutter and secure the pool with a safety winter cover in order to keep the parts to be sealed out of the water.
- For versions with a dry box: remove the gear motor, grease the stainless steel hollow shaft and store it in a dry and ventilated room. Lock the system with the crank handle supplied.
- Leave the batteries connected in the reel and do not cover the solar panel.w

SERVICING/MAINTENANCE

SPARE PARTS

Online catalogue :



<https://www.my-cfgroup.fr/fr/pieces-detachees>

REPAIR

- Do not hesitate to ask our authorised distributors for advice.
- If the power cable is damaged, it must be replaced: by the manufacturer, its after-sales service or similarly qualified persons in order to avoid danger.

REGULATIONS

WARRANTY CONDITION

log on to www.del-piscine.fr to consult all our guarantees.



<https://www.del-piscine.fr/rechercher-une-garantie>

SAFETY ADVICE

Please read the recommendations set out below with care.

WARNING

Swimming pools can represent a serious danger for your children. Drowning can happen very quickly.

Children who are close to a swimming pool need to be watched constantly and actively, even if they know how to swim.

Learn lifesaving skills.

The physical presence of an adult is absolutely essential whenever the pool is open.



Memorise the telephone numbers for the emergency services and ensure that they are displayed close to the pool.

☎18 (in France) **or 112**

FIRE SERVICE

☎15

**AMBULANCE
SERVICE**

(write the number that applies in your region)



POISON CONTROL

CENTRE


SAFETY ADVICE

- This section is by no means a replacement for common sense or individual responsibility. Its aim is not to replace the vigilance of parents and/or responsible adults, who remain the essential factor in ensuring the protection of young children.
- **Warning:** safety is only guaranteed when the cover is closed, locked and correctly installed in compliance with the manufacturer's instructions.
- The cover must systematically be closed if you are absent from home, even for a very short period.
- Check that no persons and no foreign objects are in the pool before and during opening and closing operations.
- Store the devices and/or tools needed to operate the covers out of the reach of children.
- Operation of the mechanism must only be carried out by a responsible adult.
- With the exception of movable floors, movable terraces and the covering elements provided for this purpose (e.g. gratings), do not climb, walk or jump on a safety cover.
- Take all necessary measures to prevent access to the pool for young children until the cover is repaired or when a malfunction is observed that prevents closing or in case of temporary unavailability of the equipment or the pool.
- Respect the water levels designated by the manufacturer.
- Children must not play with the appliance.
- This appliance may be used by children aged 8 and over, and by persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have received supervision or instructions concerning the safe use of the appliance and understand the hazards involved.

A child can drown in less than 3 minutes, no type of protection can ever replace the watchful eye and vigilance of a responsible adult.

RECYCLING

PACKAGING



Dispose of the packaging in line with current rules and regulations.

END OF LIFE



- Do not put your scrapped equipment or used batteries in with unsorted household waste.
- You are responsible for disposing of all of your waste, in particular electrical and electronic equipment by taking it to a collection point where recycling and valorisation are carried out.
- Certain products potentially contain substances that are dangerous for the environment, and you need to ensure that these are eliminated or neutralised.
- Make sure that you are aware of all existing recovery and collection systems.



discard the manual in line with the current regulations.



Adresses sur quefairedemesdechets.fr

NOTE

NOTE

NOTE

DEL SAS
ZA LA CROIX ROUGE
35530 BRÉCÉ - FRANCE

☎ +33 (0)9 70 72 5000 / INFO.FR@CF.GROUP

STAMP

ORIGINAL INSTRUCTIONS

/ 2026.05

A-DOTE03903.L1

A-DOTE03902.L1